

Liquid Coffee Refrigerated Dispenser



LCR-2*

Dimensions: 38" H x 12.2" W x 24.9" D
(96.5 cm H x 31 cm W x 63.2 cm D)

Features

Liquid Coffee Refrigerated Dispenser

- Refrigerated product cabinet extends product flavor profile, maintains 38°-42°F in product compartment.
- Attractive appearance and narrow (12") width.
- Dispense over 125 - 5 oz. cups per hour with a 120 volt, 15 amp electrical connection or over 500 - 5 oz. cups per hour with a 240 volt / 30 amp electrical connection.
- Accommodates all ½ gallon and most 1 gallon bag-in-box (BIB) containers.
- Refill or rinse LED lights alert the operator for concentrate or cleaning.
- Global multi-volt design is easily converted to ratings from 100 to 240 volts (50-60 hertz) eliminating the need to inventory multiple electrical configurations.
- FlavorGuard® technology continuously monitors extract-to-water ratio and assures flavor consistency.
- Easy-to-program one touch portion control model is available for self-serve applications.



LCR-2, PC*

LCR is also available with portion control

For current specification sheets and other information, go to www.bunn.com.


** International models may vary in appearance.*

Related Products

Easy Clear® EQHP-10
Product No. : 39000.0004



1/8" Replacement tube kits
Product No. : 34728.1000




Scholle BIB connector
Product No. : 35057.0000



Easy Clear® EQHP-10L
Product No. : 39000.0001

3/16" Replacement tube kits
Product No. : 34727.1000



LiquiBox QC/D II BIB connector
Product No. : 35055.0000

Easy Clear® EQHP-25
Product No. : 39000.0005



50ml Graduated Cylinder Kit
Product No. : 34843.1000
For use in calibration of pumps.



Model

LCR-2

Agency Listing



Dimensions & Specifications

Model	Product Number	Dispense Rate/Sec.		Connector Type	Volts	Amps	Heater Watts	Capacity**	Cubic Feet	Shipping Weight	Cord Attached
		1.8 oz.	2.5 oz.*								
Product Ratios											
LCR-2	34400.0036†	45:1-100:1	65:1-100:1	Scholle	120	13.2	1700	125 cups/hr.	10.9	114 lbs.	Yes***
LCR-2	34400.0037†	25:1-45:1	25:1-65:1	Scholle	120	13.2	1700	125 cups/hr.	10.9	114 lbs.	Yes***
LCR-2	34400.0038†	45:1-100:1	65:1-100:1	LiquiBox QC/D II	120	13.2	1700	125 cups/hr.	10.9	114 lbs.	Yes***
LCR-2	34400.0039†	25:1-45:1	25:1-65:1	LiquiBox QC/D II	120	13.2	1700	125 cups/hr.	10.9	114 lbs.	Yes***
					208	23.7	5000	385 cups/hr.	10.9	114 lbs.	No
					240	23.7	5800	512 cups/hr.	10.9	114 lbs.	No
†All models can be changed to these electrical configurations.											
LCR-2, PC	36500.0036†	45:1-100:1	65:1-100:1	Scholle	120	13.2	1700	125 cups/hr.	10.9	114 lbs.	Yes***
LCR-2, PC	36500.0037†	25:1-45:1	25:1-65:1	Scholle	120	13.2	1700	125 cups/hr.	10.9	114 lbs.	Yes***
LCR-2, PC	36500.0038†	45:1-100:1	65:1-100:1	LiquiBox QC/D II	120	13.2	1700	125 cups/hr.	10.9	114 lbs.	Yes***
LCR-2, PC	36500.0039†	25:1-45:1	25:1-65:1	LiquiBox QC/D II	120	13.2	1700	125 cups/hr.	10.9	114 lbs.	Yes***
LCR-2, PC	36500.0049	45:1-100:1	65:1-100:1	Scholle QC	120	13.2	1700	125 cups/hr.	10.9	114 lbs.	Yes***
					208	23.7	5000	385 cups/hr.	10.9	114 lbs.	No
					240	23.7	5800	512 cups/hr.	10.9	114 lbs.	No
†All models can be changed to these electrical configurations.											

*Unit shipped with dispense rate set at 1.8 oz./sec. Dispense rate increases to 2.5 oz./sec. if restrictor plug is removed.

Capacity measured with a 5 oz. cup. *Power cord (NEMA 5-15P) 15 Amp-120V machine only.

(30 Amp cord and plug needed for 208V and 240V models)

Electrical: 120V model requires 2-wires plus ground service rated 120V, single phase, 60 hz.

Plumbing: 20-90 psi (138-621 kPa) from a 3/8" (10 mm) or larger supply line. Unit requires a 2.2 gpm line flow capacity. A shut-off valve should be installed in the line before the unit. Install a regulator in line when pressure is greater than 90 psi to reduce pressure to 50 psi. Supplied with 3/8" (10 mm) male flare fitting.

