S6
POWERED SUBWOOFER

ConnectionTypes:



GENERAL SPECIFICATIONS:

TYPE	Powered subwoofer, sealed enclosure
AMPLIFIER TYPE	Class D
POWER OUTPUT	210 W peak power total (140 W RMS), AES
DRIVERS	6” long throw front-firing woofer
INPUTS	3.5 mm stereo mini-jack, RCA L/R
OUTPUTS	N/A
INPUT VOLTAGES	100-240 V AC, 50/60 Hz auto-switching
SIGNAL-TO-NOISE	>100 dB (typical A-weighted)
THD+N	<0.2% at all power settings
CROSSTALK	N/A
FREQ. RESPONSE	33Hz - 132kHz (+/-1.5dB)

WHAT’S IN THE BOX:

-S6 powered subwoofer
-AC power cord
-Mini-jack audio cable
-RCA audio cable
-Microfiber subwoofer bag
-Microfiber cable bag
-Setup guide

ENVIRONMENTAL REQUIREMENTS:

Operating temperature: 32 degrees F to 95 degrees F, Non-operating temperature: -4 degrees F to 113 degrees F, Relative humidity: 5% to 95% non-condensing

PRODUCT DIMENSIONS

Product Weight - 15.4 lb (6.98 kg)
Product Dimensions - 10"H x 8.7"W x 10"D
Product Shipping Weight - 18.2 lb (8.26 kg)
Product Shipping Dimensions - 13” x 13” x 14”

HAND CRAFTED FINISH:

Matte Black **S6-BLK**
Red **S6-RED**
Walnut **S6-WAL**
Grey **S6-GRY**
Matte Green **S6-GRN**
Matte White **S6-WHT**
Limoncello Yellow **S6-YELLOW**